

Silicone Sponge Tube

closed cell smooth finish



Silicone Sponge Tube

Silicone sponge tube not only maintains the advantage of silicone sponge, but also can be more flexible for producing complex cross-sectional shapes (such as irregular pipes, porous structures) continuously to meet demanding need

Silicone Sponge Tube

Type Description	Silicone Sponge Tube	Test Method
CODE	SPT	
Environmental Test	RoHS	ASTMD2240
Density,g/cm ³ ,+/-0.05	0.	ASTMD1056
Cell Structure	closed cell	
Surface skin	Smooth	
Tensile Strength,kpa	>400	ASTMD412
Elongation,%	>80	ASTMD412
Compression Set% (100°C*22h) ,Ma	<4	ASTMD1056
Compression Deflection25%,kpa	75-125	ASTMD1056
Water Absorption,%	<4	ASTMD1056
Thermal Conductivity,W/M.K	0.08	
Tempertaure Ranger,	-55--200	
UV/ozone Resistance	Excellent	
Volume Resistivity Ohm-mm	> 1.0*10 ¹⁵	
Flame Resistance	Nil	UL94
Color	Red/Black/Grey /White	
Thichness Range,m	0.8-50	
Continous Rolls ,m	< 20	
Width Range ,m	1-1000	
Standard Width,mm	1000	
Standard length,m	10	

Note: 1.thickness above 10mm is made by laminated bonding.

2.The data is only for references